

FRONT WHEEL

CHAS



FRONT WHEEL

- | | |
|------------------|--------------------|
| ① Wheel axle | ⑪ Plain washer |
| ② Hub dust cover | ⑫ Meter clutch |
| ③ Collar | ⑬ Drive gear |
| ④ Oil seal | ⑭ Brake shoe comp |
| ⑤ Bearing | ⑮ Brake camshaft |
| ⑥ Spacer flange | ⑯ Camshaft lever |
| ⑦ Spacer | ⑰ Cap |
| ⑧ Spoke | ⑱ Brake shoe plate |
| ⑨ Oil seal | ⑲ Driven gear |
| ⑩ Circlip | |

BASIC WEIGHT:
WITH OIL AND
FULL FUEL
TANK

81 kg (179 lb)
82 kg (181 lb)
FOR ENGLAND

MAXIMUM
LOAD*

241 kg (531 lb)

COLD TIRE PRESSURE


FRONT

250 kpa
(2.5 kg/cm², 36 psi)

REAR

250 kpa
(2.5 kg/cm², 36 psi)

* Load is the total weight of cargo rider, passenger, and accessories.




REAR WHEEL



REAR WHEEL

- | | |
|--------------------|---------------------|
| ① Wheel axle | ⑨ Brake shoe lining |
| ② Chain puller | ⑩ Oil seal |
| ③ Spacer | ⑪ Bearing |
| ④ Cap | ⑫ Plain washer |
| ⑤ Brake shoe plate | ⑬ Spacer |
| ⑥ Camshaft lever | ⑭ Oil seal |
| ⑦ Bolt | ⑮ Collar |
| ⑧ Camshaft | ⑯ Tension bar |



FRONT FORK

CHAS




FRONT FORK


- | | | |
|----------------|-------------------|----------------|
| ① Cap bolt | ⑥ Outer cover | ⑪ Circlip |
| ② Plain washer | ⑦ Spring seat | ⑫ Plain washer |
| ③ O-ring | ⑧ Front fork boot | ⑬ Oil seal |
| ④ Guide cover | ⑨ Spring | ⑭ Slide bush |
| ⑤ Gasket | ⑩ Spring seat | ⑮ Inner tube |
| | | ⑯ Outer tube |

A	FORK OIL:
B	CAPACITY (EACH LEG): 160 cm ³ (5.64 Imp oz, 5.41 US oz)
C	TYPE: Fork oil 10W or Equivalent
D	SPRING FREE LENGTH LIMIT: 151 mm (5.94 in)

30 Nm (3.0 m•kg, 22 ft•lb)




STEERING HEAD AND HANDLEBAR




STEERING HEAD AND HANDLEBAR

- | | |
|---------------------------|------------------------|
| ① Handlebar | ⑦ Bearing race (Upper) |
| ② Handlebar upper bracket | ⑧ Ball bearing |
| ③ Handlebar lower bracket | ⑨ Bearing race (Lower) |
| ④ Handlebar crown | ⑩ Steering stem |
| ⑤ Ring nut | ⑪ Steering lock |
| ⑥ Ball race cover | ⑫ Headlight stay |




REAR SHOCK ABSORBER AND SWINGARM



REAR SHOCK ABSORBER AND SWINGARM

- ① Chain cover
- ② Thick washer
- ③ Rear shock absorber
- ④ Swingarm
- ⑤ Bush
- ⑥ Pivot shaft



ELECTRICAL COMPONENTS


ELEC



ELECTRICAL COMPONENTS

- ① Wireharness
- ② Main switch
- ③ Ignition coil
- ④ Spark plug cap
- ⑤ Diode
- ⑥ Reserve fuse
- ⑦ Main fuse
- ⑧ Battery

SPECIFICATIONS	RESISTANCE
IGNITION COIL: PRIMARY	1.4 ~ 1.8Ω
SECONDARY	6.0 ~ 7.3kΩ
SPARK PLUG CAP:	5kΩ



A	BATTERY:
B	CAPACITY: 6V4AH
C	SPECIFIC GRAVITY: 1.260


ELECTRICAL COMPONENTS

ELEC



- ① Horn (Except for Holland)
- ② Front brake switch
- ③ Flasher relay
- ④ Rear brake switch
- ⑤ Neutral switch
- ⑥ Contact breaker assembly
- ⑦ Condenser
- ⑧ Charging coil
- ⑨ Source coil
- ⑩ Rotor assembly

SPECIFICATIONS	RESISTANCE
SOURCE COIL: BLACK—BLACK/WHITE	1.4 ~ 2.0Ω
CHARGING COIL: BLACK—YELLOW BLACK—GREEN/RED	0.4 ~ 0.6Ω 0.3 ~ 0.5Ω



CABLE ROUTING

SPEC




CABLE ROUTING

- ① Lever holder (Right)
- ② Brake cable
- ③ Meter bracket
- ④ Lever holder (Left)
- ⑤ Clutch cable
- ⑥ Handlebar switch (Left) lead

- ⑦ Handlebar switch (Right) lead
- ⑧ Speedometer cable
- ⑨ Clamp
- ⑩ Front brake switch lead
- ⑪ Band

Ⓐ Pass between meter bracket and handlebar.



CABLE ROUTING



SPEC



- ① Speedometer assembly
- ② Main switch
- ③ Headlight unit assembly
- ④ Wireharness
- ⑤ Clutch cable
- ⑥ Air cleaner case

- ⑦ Band
- ⑧ Spark plug lead
- ⑨ Brake cable
- ⑩ Speedometer cable
- ⑪ Clamp
- ⑫ Fuel hose

- A** For Belgium and England
- B** Pass through downtube stay



CABLE ROUTING

SPEC



- ① Band
- ② Throttle cable 2
- ③ Oil pump cable
- ④ Clutch cable
- ⑤ Fuel hose
- ⑥ Throttle cable 1
- ⑦ Vacuum hose (Carburetor)
- ⑧ Oil hose

[A] Fit wire cylinder on to frame tab.

